



Turf-Slab [80mm]

With a thickness of 80mm (3.15"), Oaks Turf-Slab is the perfect fit for areas prone to soil or turf erosion. Designed to complement either a granular or natural turf fill, these stones provide stability to pond linings, vehicular access roads, event parking areas and environmentally sensitive locations. In natural color, Turf-Slab can also be mechanically installed, reducing both time and labor costs.



Turf-Slab, Natural

Turf-Slab [80mm]



Nueva® Collection

SIZE



Width 400mm (15.76")
Length 600mm (23.62")

COLOR



NATURAL

SPECIFICATIONS

Bundle Specifications

TURF-SLAB	Layers	Sq. Ft.	Lin. Ft.	Pieces	Weight	Sections	Sq. Ft.	Lin. Ft.	Pieces	Weight
16x24	6	77.4	59	30	1860	No Sections available				

Per Section Specifications

FEATURES:

- Turf-Slab is manufactured with spacer bars and chamfered edged to prevent chipping
- Each Turf-Slab unit has a 40% void area to allow vegetation growth
- Turf-Slab units are capable of supporting vehicular traffic when installed over a proper base layer

TYPICAL USES:

- Cottage Parking
- Emergency & Service Vehicle Access Routes
- Slope Erosion Protection
- Retention Pond Linings and Vehicular Access Roads
- Ditch & Channel Linings
- High Use Turf Areas like Event Parking and Public Parking Areas
- Environmentally Sensitive Area Erosion Protection
- Small Lake Boat Launching Ramps

All Oaks Landscape products fully meet or exceed the latest version of CSA A231, ASTM C936, ASTM C1372 or ASTM C1782 as applicable to the specific product and area of sale.

BramptonBrick.com

CA - 1.800.709.OAKS (6257)

US - 1.800.876.OAKS (6257)

Members of:



Product representations shown in this publication are intended to convey the general color, texture and appearance of the product. Variations may occur in the manufacturing and printing process. Always select from an actual product sample.